



### 封口型冲压外圈滚针轴承

### Drawn Cup Needle Roller Bearing With Closed Ends

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	D	C	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
3	BK0306TN1		3	6.5	6	1230	840	28800	48000	0.00080
6	BK0609		6	10	9	2850	2600	18000	27000	0.00260
7.938	MJ-551		7.938	12.7	7.92	2400	2300	18000	27000	0.00460
8	BK0810	55941/8	8	12	10	3800	3950	18000	27000	0.00330
	BK081410		8	14	10	3000	3200	18000	27000	0.00647
9	BK09X16X13.45/YB1	009-0080-002-064	9	16	13.45	4550	3800	18000	27000	0.00820
9.525	MJ-661		9.525	14.288	9.52	2600	2700	18000	27000	0.00499
10	BK1010	55941/10	10	14	10	4400	5100	15000	24000	0.00430
	BK1012		10	14	12	4600	5900	15000	24000	0.00568
12	BK1210	BK121610	12	16	10	3800	4900	12000	21000	0.00515
	BK1212	35942/12	12	18	12	6500	7300	12000	20000	0.01030
15	BK1512	35941/15	15	21	12	7900	9400	9600	16000	0.01270
	BK15X21X15.5/YA1		15	21	15.5	7500	9100	9600	16000	0.01527
	BK152215		15	22	15	7400	9000	9600	15000	0.01740
16	BK1616		16	22	16	10900	15300	9600	16000	0.01760
	BK162217-RS	SZ-435	16	22	17	8200	11800	9600	16000	0.02020
17	BK1712	35941/17	17	23	12	7900	10300	8500	15000	0.01450
	BK172324-RS		17	23	24	13100	21900	8500	15000	0.02680
20	BK2016	55941/20	20	26	16	12700	20100	7200	13000	0.02230
22	BK222822-RS		22	28	22	12900	13600	6500	10000	0.02830

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	D	C	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
25	BK2516		25	32	16	14900	22000	6500	10000	0.02320
	BK2526		25	32	26	25500	45000	6500	10000	0.04634
30	BK3026		30	37	26	23900	48700	6500	10000	0.06000
	BK303727		30	37	27	24800	51100	5600	8000	0.05884
40	BK4020	65941/40	40	47	20	25500	52000	4500	6300	0.06200