



## 冲压外圈满针滚针轴承

### Drawn Cup Needle Roller Bearings , Full Complement

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	D	C	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
7.938	M-551		7.938	12.7	7.92	3600	3900	6200	9500	0.00350
	Y-57		7.938	12.7	11.13	3500	3800	6200	9500	0.00500
8	FY081210		8	12	10	6100	8300	6200	9500	0.00424
	FH-810	20942/8	8	14	10	5200	5200	4900	7400	0.00700
9.525	SN65		9.525	14.288	7.94	5300	6800	4800	7100	0.00441
	SN 66		9.525	14.288	9.52	6500	8700	4800	7100	0.00585
	Y-68		9.525	14.29	12.7	9000	13300	4800	7100	0.00750
	Y-610		9.525	14.29	15.88	10900	17100	4800	7100	0.00880
10	BK10159.5V	SZ-465	10	15	9.5	6100	8800	4800	7100	0.00670
	FY-101609		10	16	9	6900	8200	4800	7100	0.00680
	MFY-10X16.02X9.5		10	16.02	9.5	7000	8600	4800	7100	0.00785
12	F-121712	941/12	12	17	12	8400	11900	4800	7100	0.00800
13	MFY-131912	SZ-412	13	19	12	8300	11300	4700	6800	0.01200
14	F-1413	947/14	14	20	13	10500	15000	4100	5800	0.01200
	MFY-142213		14	22	13	14400	17900	4100	5800	0.01836
14.288	B-96		14.288	19.05	9.52	6900	10600	4100	5800	0.00687
15	FY-152007		15	20	7	5600	8600	4100	5600	0.00606
15.5	FY-16.52018	SZ-411	15.5	20	18	16300	31000	4000	5600	0.02070
15.88	B-108		15.88	20.64	12.7	10000	17500	4000	5600	0.01015
	YH-108		15.88	22.22	12.7	14700	21800	4000	5600	0.01467
	BH-108	6559256	15.88	22.22	12.7	12400	17700	4000	5600	0.01373
19.05	HK193406V	019-0080-001-064	19.05	34.131	6.35	11800	9600	4000	5600	0.02166
20	F-2012	30941/20	20	26	12	11900	18800	3000	4300	0.01800
	MF-2012	36941/20	20	26	12	11900	18800	3000	4300	0.01670
	F-202625	943/20	20	26	25	20500	35500	3000	4300	0.03300
	FY-202820		20	28	20	26000	38000	3000	4300	0.03745
21	HK213527V		21	35	27	47400	61500	3000	4300	0.10380
22.225	B-1416		22.225	28.575	25.4	20140	31180	3000	4300	0.03888

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	D	C	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
25	Y-25338	Y25338	25	33	8	12200	16800	3000	4300	0.01670
	HK253316V	SZ-470	25	33	16	19600	31000	3000	4300	0.03570
25.4	B-168		25.4	31.75	12.7	16000	28300	25800	4300	0.02088
	B-1610		25.4	31.75	15.88	20800	39600	25800	4300	0.02681
	B-1612		25.4	31.75	19.05	25100	50400	25800	4300	0.03271
	BH-168		25.4	33.34	12.7	16000	24400	3000	4300	0.02640
26	FY-26325		26	32	5.3	6000	9300	3000	4300	0.00940
28.58	B-188		28.58	34.92	12.7	17200	31900	25800	4300	0.02258
	BH-1812		28.58	38.1	19.05	30780	51152	25800	4300	0.05420
30	F-303825	SZ-476	30	38	25	36100	73600	2500	3800	0.06120
	FY-303825		30	38	25	42100	89600	2500	3800	0.06895
	F-304025	SZ-475	30	40	25	39000	69800	2500	3800	0.08190
30.7	HK30.7×58×19.5V		30.7	58	19.5	60300	61800	20800	3800	0.20885
31.75	Y-2012		31.75	38.1	19.05	29600	70000	2300	3600	0.04100
	BH208		31.75	41.275	12.7	16300	23600	2300	3600	0.04050
35	F-354325	942/35	35	43	25	38700	86200	2200	3200	0.07200