



NA,NKI,NKIS

NA...A
NKI...A
NKIS...A

NA,NKI,NKIS
 $d \leq 7$

NA0

有内圈滚针轴承

Needle Roller Bearing With Inner Ring

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	d	D	B	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
9	NK19/12		9	19	12	6800	6300	17200	24800	0.01514
10	NA4900A	4524900	10	22	13	5900	7400	14400	21600	0.02730
	NAVP5900M/P6S1	E54700HT2	10	26	17	7800	8400	14400	21600	0.05400
12	NA4901A	4524901	12	24	13	5800	6200	13500	20700	0.02600
15	NA4902A	4524902	15	28	13	6100	8600	12000	18000	0.03400
	NA153312		15	33	12	12200	14100	13500	20700	0.05450
17	NA4903	4524903	17	30	13	9200	13500	10000	16000	0.04050
	NA173017		17	30	17	12000	18900	10000	16000	0.05225
20	NK120/16		20	32	16	14300	20800	12000	18000	0.04835
	NK120/20		20	32	20	17200	26500	12000	18000	0.06293
	NA203316		20	33	16	14500	21200	12000	18000	0.05675
	NA0203517	NAF203517	20	35	17	15100	25400	9600	14400	0.07310
	NA4904	4524904	20	37	17	20600	27700	9600	14400	0.07980
22	NK122/16	NA223416	22	34	16	13300	21900	9300	14000	0.05000
	NA49/22	45449/22	22	39	17	24000	30300	9100	13600	0.08150
	NA49/22/P6	E45449/22	22	39	17	21000	29300	9100	13600	0.08200
25	NK125/20		25	38	20	23100	36300	9300	14400	0.08170
	NA4905	4524905	25	42	17	22900	29600	9300	14000	0.09381
28	NK128/20	NA284220	28	42	20	24700	39700	8000	14000	0.09400
	NA49/28/P6	E45449/28	28	45	17	20700	29700	8000	11900	0.09840
30	NA0304517	NAF304517	30	45	17	18000	35700	7300	10800	0.01000
	NK130/20/P6	ENA304520	30	45	20	23200	43700	7300	10800	0.11200
	NA4906		30	47	17	25000	35500	7300	13000	0.10100
	NA4906/P6		30	47	17	23700	36600	7300	10800	0.11150
35	NA4907	4524907	35	55	20	21600	37200	7300	11000	0.17000
	NK1S35	544807	35	58	22	35600	53700	5500	10000	0.22000
40	NK140/20	NA405520	40	55	20	29100	56200	5700	8400	0.14200
	NK140/30	SZ-413	40	55	30	35200	80700	5700	8400	0.21600
	NA4908	4544908	40	62	22	41100	66600	5400	8000	0.24000

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	d	D	B	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
45	NK145/35		45	62	35	52000	108800	5000	7600	0.33200
	NA4909A	4524909	45	68	22	32600	55200	4900	7300	0.27100
	C3GNA456235		45	62	35	42000	58000	4900	7300	0.30980
50	NA4910	45544910	50	72	22	41400	71600	4400	6600	0.27400
55	NK155/35	544711	55	72	35	65900	143500	4300	6400	0.37900
	NA4911A	4524911	55	80	25	38700	74400	4100	6000	0.39300
	NA4911A/C2	C2G4524911	55	80	25	63100	101600	4100	6000	0.42680
60	NA4912A	4524912	60	85	25	41600	82200	3800	50600	0.42600
65	NA4913	4524913	65	90	25	42700	87500	3500	5300	0.45600
	NA4913A/P62	C2E4524913	65	90	25	42700	87500	3500	5300	0.48950
70	NK170/35		70	95	35	78000	184000	3600	6000	0.73700
	NA4914A	4524914	70	100	30	53300	121000	3200	4800	0.72800
	NA4914A/C2	C2G4524914	70	100	30	89300	155800	3200	4800	0.80540
85	NK185/36	NA8511536	85	115	36	105050	216800	2700	4000	1.04000
100	NA4920A	4524920	100	140	40	97100	250400	2200	3200	1.93000